

036707 367070

UNITED STATES PATENT APPLICATION

OF

AWELE NDILI

FOR

SYSTEM FOR CONVERTING WIRELESS COMMUNICATIONS FOR A  
MOBILE DEVICE

PREPARED BY WILSON SONSINI GOODRICH & ROSATI

## BACKGROUND OF THE INVENTION

### Related Applications

This application claims priority to U.S. Patent App. No. 60/163,115, entitled *Portal Configuration in Wireless Medium*, to Moeller et al., filed November 2, 1999; to U.S. Patent App. No. 09/513,554, entitled *System and Automatic Data Retrieval on an Internet Protocol Network*, to Ndili et al., filed on February 25, 2000; and to U.S. Patent App. No. 60/204,502, entitled *System for Providing Network Content to Wireless Devices*, to Ndelie et al., filed May 16, 2000; all of which are incorporated by reference herein.

### 10 Field of the Invention

This invention relates to the field of wireless communications. In particular, the invention relates to wireless communications exchanged between a mobile device and a network site using a language conversion engine.

### Description of the Related Art

15 Wireless technology now enables mobile devices to wirelessly couple to networks such as the Internet. The mobile devices can couple to the networks to receive information and content.

Typically, mobile devices are programmed to use a single language. The language use by the mobile device determines which network sites can be accessed. In some countries and geographic regions, mobile devices favor one type of language. Information providers typically structure network sites to provide content to the mobile devices using the language that is more prevalent in that geographic region. This makes it difficult for devices using other languages to have the same breadth of network access.

5

10

[illegible]

## BRIEF DESCRIPTION OF THE FIGURES

FIG. 1 is a block diagram illustrating a system for exchanging communications between a mobile device and a network site, each of which communicate using different languages, under an embodiment of the invention.

5        FIG. 2 is a flow process for coupling the mobile device to a conversion engine, under an such as described with FIG. 1.

FIG. 3 is a block diagram illustrating a system for coupling a mobile device to a network site having one or more internal links, where the mobile device and network site communicate using different languages, under an  
10        embodiment of the invention.

FIG. 4 is a flow process for coupling the mobile device to the conversion engine to enable the mobile device to retrieve content from a network site programmed in a different language, where the network site includes internal links that are to be provided to the mobile device, under an embodiment such as  
15        described with FIG. 3.

FIG. 5 is a block diagram illustrating a system for exchanging communications between the mobile device and the network site, each of which communicate using different languages, where the network site includes multiple input features for each page, under an embodiment of the invention.

20        FIG. 6 is a flow process for coupling the mobile device to the conversion engine to enable the mobile device to retrieve content from a network site programmed in a different language, where the network site provides multiple input features for each page, under an embodiment such as described with FIG.

FIG. 7 is a block diagram illustrating a system for exchanging communications between the mobile device and the network site, where the system can identify the mobile device and determine if conversion is necessary, under an embodiment of the invention.

- 5           FIG. 8 is a flow process for segmenting a page from a network to fit on a small display screen of a mobile device, under an embodiment such as described with FIG. 7.

2007-07-27 14:00:00

## DETAILED DESCRIPTION

### A. System Overview

Embodiments of the invention provide a conversion engine to enable mobile devices to retrieve content from network sites, where the mobile device  
5 and the network site use different languages. In one application, a conversion engine is used to couple mobile devices using a first language to a network site using a second language. This allows for a device that is operable using a first language to be coupleable to network sites that use either the first language or a second language.

10 In one embodiment, a mobile device is operable in a first wireless language. The mobile device is coupleable to the conversion engine to access network sites that would otherwise require the mobile devices to be operable in a second language.

Mobile devices include devices that are capable of wireless  
15 communications. Preferably, the mobile device is configured to communicate using wireless access protocol (WAP). The language used by the mobile device may be anyone of the languages mentioned in this application. Examples of mobile devices include wireless devices such as cell phones, smart phones, handheld computers and personal digital assistants (PDAs) that use wireless  
20 communications. Specific examples include Sprint PCS phones, Palm VII, and other PDAs that use wireless modems.

In one specific implementation, the mobile device is WAP enabled and programmed in a Handheld Device Markup Language (HDML). The WAP

device is coupleable to the conversion engine to retrieve information from network sites that are otherwise programmed to communicate with mobile devices using Compact Hypertext Markup Language (CHTML).

An advantage provided by an embodiment of the invention is that  
5 mobile devices are enabled to communicate with different types of network sites, including network sites using languages other than those of the mobile devices. Thus, mobile devices have access to a greater number of network sites.

Another advantage is that mobile devices using a first language can be made to access network sites suited for mobile devices that are programmed to  
10 communicate in a second language. Some countries in particular favor one wireless language for WAP devices over other wireless languages. For example, in Japan, most WAP devices use CHTML to communicate to network sites, while in other countries, most WAP devices use HDML. For example, currently in some countries such as Japan, HDML devices are precluded from  
15 communicating with the majority of available network sites which use CHTML.

An advantage of the invention is that WAP devices using one type of wireless language (i.e. HDML) can couple to network sites which can only communicate in another wireless language (i.e. CHTML).

Another advantage provided by an embodiment of the invention is that  
20 mobile device can retrieve content and information from network sites programmed with different languages. The mobile device may retrieve content from network sites programmed in different languages. The content may be retrieved on-the-fly, so that information from the different network sites is made

00664E-10100

available to the user of the mobile device automatically in response to the user's request.

An embodiment of the invention includes a system for exchanging communications between a mobile device and a network. The system includes a conversion engine. The conversion engine communicates with a mobile device to receive a request to access a network site. The mobile device communicates in a first language, and the network site includes resources programmed in a second language. The conversion engine converts the request from the mobile device from the first language to the second language. The conversion engine then retrieves content from the network site. To make the content available for the mobile device, the conversion engine converts the content be renderable on the mobile device in the first language.

The term network page refers to content rendered from a network site. When rendered, the network page may in fact appear on more than one screen shots of the mobile device. Currently, mobile devices can communicate with network sites using one language. Embodiments of the invention expand the ability of mobile devices to communicate with network sites using two or more languages.

As used herein, languages refers to programming used to coupling network sites and mobile devices. Examples of languages include HTML, CHTML, wireless markup language (WML), and HDML.

Conversion engine includes an assembly of one or more modules. The conversion engine is preferably located on a server or other computer. As used herein, modules includes programming that performs a stated function. Modules



may be in the form of hardware, software, firmware, or a combination thereof. One or more modules and other parts of the conversion engine may be distributed between different computers.

Content refers to information that can be rendered when communication with the network site is established. Examples of content include pages rendered from network sites, text messages, links to other network sites, and logos. Another example of content includes media, such as provided by streaming media, including video and/or audio.

Another embodiment of the invention includes method for exchanging communications between a mobile device and a network site. A request to access a network site from a mobile device is received. The request is structured in a first language. A content from the network site is retrieved in the second language. The content is signaled to the mobile device in the first language. In an embodiment, the first language allows for a single input entry per page rendered from the network site, and the second language allows for multiple input entries per page rendered from the network site.

For reference, CHTML is a W3 Consortium defined protocol for mobile devices. One notable characteristic of CHTML is that multiple input and entry fields can be provided on mobile devices that use this protocol. Another notable characteristic of CHTML is that is allows for diverse user interaction using select and limited input mechanisms, typically one or more buttons on the mobile device.

CHTML was adopted as a well-defined subset of Hypertext Markup Language (HTML), but scaled to better accommodate small information

appliances such as smart phones and personal digital assistants (PDAs). Small information appliances have several limitations, including limited memory, low power processors, small displays, monochrome, and restricted input devices. Typically, CHTML excludes features such as JPEG images, tables, image maps,  
5 multiple character fonts and styles, etc.

FIG. 1 is a block diagram illustrating a basic system architecture, under an embodiment of the invention. A system 100 includes a conversion engine 50. A mobile device 60 is coupled to the conversion engine 50 via a wireless connection. The conversion nodule 50 has access to a plurality of network sites  
10 30 over network 35. The plurality of network site 30 may provide content and/or information in one or more formats. Reference to a particular format or format conversion is intended to mean that communications intended for or received from a network site are structured according to a designated language, such as industry standard programming for providing network pages to  
15 terminals and mobile devices. An example of network 35 includes the Internet. As an example, network sites 30 for use with an embodiment of the invention includes web sites with resources, files or other information structured to be rendered using HTML or CHTML.

The mobile device 60 signals a request 1 for content from a network site  
20 30. The specific network site 30 may be a selection of the user of mobile device 60. The request may be initiated by manipulating or interacting with a user-interface feature of the mobile device 60. Typically, users may initiate request 1 using graphic input feature, an application button, or a combination thereof. For example, the user may select a bookmark corresponding to a favorite network

page. Once initiated, request 1 is sent to conversion engine 50 via a wireless network.

Communications between the mobile device 60 and conversion engine 50 may be made via a wireless network 38. The request 1 may be transmitted to an uplink server (not shown) before being forwarded to a server where the conversion engine resides. The connection between the uplink server and the server hosting the conversion engine may be through a land based communication line. The conversion engine 50 may be located on one or more servers or computer systems coupled to the uplink server. The uplink server may be selected for communication with mobile device 60 based on the geographical location of mobile device 60.

In an embodiment, mobile device 60 is configured to communicate with a network using a first language. Therefore, request 1 is a communication transmitted using the first language. The network site 30 is configured to communicate with a mobile device (or other terminal or device) using a second language, where the second language is different than the first language. For example, the first language may be HDML, and the second language may be a version of HTML, and preferably CHTML.

The conversion engine converts request 1 from the first language into the second language. The conversion engine 50 forwards request 2 to the network site 30. The request 2 is used to access information and content from network site 30. In response to signaling request 2, conversion engine 50 is able to retrieve content 3 from network site 30. The content 3 is converted by

conversion engine 50 into a newly formatted content 4. The newly formatted content 4 is signaled to mobile device 60.

FIG. 2 is a flow process illustrating communications exchanged between mobile device 60 and network site 30, under an embodiment of the invention.

5 Reference to elements of FIG. 1 with description of this flow process is intended only to illustrate an exemplary configuration for the embodiment.

In step 80, conversion engine 50 receives a request from mobile device 60. The request is formatted in a first language used by the mobile device 60 for communications. For example, mobile devices 60 is assumed to use HDML to  
10 communicate with network sites on the Internet. Without use of conversion engine 50, mobile device 60 would only be able to access network sites containing files programmed in an HDML format. The conversion engine 50 may include a network interface (not shown) to receive the communications from the mobile device.

15 In step 82, the request from mobile device 60 is converted to the second language. The request may be converted by a conversion component (such as a module or program) of the conversion engine 50. The request is converted to the language used by network site 30. In an embodiment, the language of the network site 30 is CHTML.

20 In step 84, the converted request is signaled to network site 130. Then in step 86, a response to the request is retrieved (or fetched) by the conversion engine 50. In step 88, the conversion component of the conversion engine 50 converts the content retrieved from the network site into an HDML format. In

step 90, the content received as a response from network site 30 is signaled to mobile device 60.

#### B. Converting Internal Links Between Wireless Languages

FIG. 3 is a block diagram illustrating a system 200, under another  
5 embodiment of the invention. The system 200 includes a conversion engine  
150 that is coupleable to mobile device 160 via a wireless network 138. The  
conversion engine 150 is also coupleable to network sites 130 via a network  
135.

The system 200 illustrates an embodiment where internal links on the  
10 network site 130 are identified, then structured for mobile device 160. When  
structured, the internal links are renderable on the display of the mobile device  
in HDML. Further, the structured internal links are associated with an address  
that can be signaled to conversion engine 150 when the user of the mobile  
device 160 selects the internal link. The mobile device 160 is assumed to  
15 communicate using HDML, while network site 130 is assumed to communicate  
in CHTML.

In an embodiment, mobile device 160 signals request 11 to conversion  
engine 150 to retrieve content from network site 130. Request 11 is coded in  
HDML. The conversion engine 150 restructures the request from mobile device  
20 160 and signals request 12 to network site 130 using CHTML. The conversion  
engine 150 receives content 13 from network site 130 that is coded in CHTML.  
The conversion engine 150 formats the content from the network site into  
HDML. The content is then transmitted with signal 14 to mobile device 160.

The network site 130 may include a plurality of internal links. As used herein, internal links of any network site are selectable representations of network addresses provided on that network site. For example, a page rendered from a network site may include links to other web sites.

5           FIG. 3 illustrates network site 130 to include internal links to network sites 132, 133 and 134,. The internal links are selectable when content from network site 130 is rendered. As such, network sites 132, 133, 134 are internal links for network site 130. In FIG. 3, network sites 136, 137, and 138 represent internal links to network site 133. Thus, network sites 133 are internal links to  
10   network site 130. It is possible for a network site to have its own link as an internal link.

          The content 13 would be renderable on a CHTML type device to provide content and information from network site 130. The content 13 would include selectable internal links to enable the CHTML type device to couple to  
15   other network sites. For an embodiment such as described with FIG. 3, conversion engine 150 identifies internal links from content 13. When converting content 13, conversion engine 150 restructures the internal links into HDML so as to be selectable on mobile device 160. Moreover, the internal links are structured so as to be selectable to signal in HDML the address of the  
20   corresponding network address 132, 133, 134 to conversion engine 150. The conversion engine 150 restructures the internal links to appear on the mobile device 160 as selectable user-interactive features. When a user-interactive feature is selected, the internal links signal conversion engine 150 to access the selected internal network sites 132, 133, 134 of network site 130.

A request 15 represents a selection made by the user of mobile device 160 to receive content from network site 133, located by the corresponding internal link displayed on mobile device 160 with content 14. The request 15 is signaled to conversion engine 150 in HDML. The conversion engine 150  
5 converts request 15 to CHTML, which is then forwarded to network site 132 as CHTML request 16. The network site 133 retrieves CHTML content 17 from network site 132. The conversion engine 150 then converts CHTML content 17 to an HDML format. Signal 18 includes content from network site 133 in HDML. Signal 18 may include internal links located on network site 133.

10 FIG. 4 is a flow processes for illustrating communications exchanged between mobile device 160 and network site 130, under an embodiment of the invention. Reference to elements of FIG. 3 with description of this flow process is intended only to illustrate exemplary configurations and components for use with this embodiment.

15 In step 270, mobile device 160 requests content from network site 130. The request is signaled using HDML. The conversion engine converts the request to CHTML in step 272. In step 274, request for content is signaled to network site 130, formatted in CHTML. A network page is returned from network site 130 in step 276. The network content may be retrieved or fetched  
20 after the request is signaled in step 274.

In step 278, conversion engine identifies links located on the network page retrieved from network site 130. The links identified on the network page correspond to internal links 132, 133, 134. In step 280, the network page is converted from CHTML to HDML. In step 282, the internal links are formatted

to be displayed and selectable by mobile device. Specifically, the links are formatted to locate the internal network sites 132, 133, and 134 upon being selected. The addresses each link signals by its selection is formatted to be signaled in HDML to conversion engine 150.

5           In step 284, the network page retrieved from network site 130 is signaled to mobile device 160. The network page includes the formatted internal links, which are displayed on mobile device 160 for further selection.

          After the page for network site 130 is rendered on mobile device 160, conversion engine 150 receives a request from mobile device 160 in step 286.

10          The request is for a network page located by an internal link on network site 130. The request is in HDML. The rendered network page may include user-interactive features to allow the user of mobile device 160 to select an internal link appearing on that network page. For example, the internal links may appear as icons on the display of the mobile device 160.

15           In step 288, the request is converted from HDML to CHTML. It will be appreciated that the request for the internal link is treated by conversion engine 150 in the same manner as the request for network site 130. This is possible because conversion engine 150 converted the internal links in step 282 to be selectable to locate corresponding network sites for conversion engine 150.

20           In step 290, a network page is retrieved for the selected internal link. The network page is retrieved in CHTML. The retrieved network page is converted to HDML in step 292. The network page located by the internal link is signaled to the mobile device 160 in step 294.



One advantage of the invention is that mobile device 160 is provided internal links for each rendered network page. The internal links provided are selectable to locate a corresponding network page without having to access the previous network site that provided the page being rendered on the mobile  
5 device 160.

### C. Converting Input Between Wireless Languages

FIG. 5 illustrates another embodiment of the invention in which input features included in the network page that is retrieved from a network site are formatted with other content and rendered on mobile device 160. The system  
10 500 includes conversion engine, mobile device 460, and a plurality of network site 432. The conversion engine 450 is coupleable to the mobile device 460 and to the plurality of network sites 432. A wireless network 408 used to couple the mobile device 460 to the conversion engine 450. The wireless network may include an uplink server and a land communication system. A network 405 may  
15 be used to couple conversion engine 450 to network sites 430. An example of network 405 is the Internet.

The system 500 illustrates an implementation for converting input features from one language to another language. Specifically, wireless device 460 is assumed to communicate with network sites and other devices using a  
20 language that is limited in the number of input features that can be displayed. In one embodiment, wireless device 460 communicates in HDML, while network site 432 is assumed to use CHTML. Current versions of HDML are limited to displaying a single input feature per rendered network page. That is, when the

HDML device retrieves a network page from a network site programmed in HDML, that network page can only have one text entry field, menu item, check-field etc.

In contrast, CHTML can be used to display multiple input features per rendered network page. For example, CHTML pages may display an application  
5 containing multiple input fields, including first name, last name, age, credit card number, etc.

One advantage provided with this embodiment is that it recognizes that when a CHTML network page is rendered on an HDML device, one or more  
10 input features provided on the network page may be unavailable. The system 500 enables all input features on a CHTML network site to be available when the page for that site is rendered on an HDML device.

With reference to FIG. 5, conversion engine 450 receives request 111 from mobile device 460. The request 111 is for a network page provided by  
15 network site 430. The conversion engine 450 converts the request 111 from HDML to CHTML. The request 112 is formatted in CHTML and directed to network site 430. The conversion engine 450 retrieves a network page 113 from network site 430. The network page is retrieved in CHTML. The conversion engine 450 converts the network page 113 to HDML. The network page is  
20 signaled as content 114 to mobile device 460.

In an embodiment, the page provided by network site 430 includes multiple input features. Input features include, for example, text-entry fields, icons, check-fields assigning Boolean values, and selectable items provided in a menu. As mentioned, current versions of HDML permit mobile device 460 to

display or otherwise render only one input feature from each network page retrieved from network site 430.

In an embodiment such as shown by FIG. 5, the conversion engine 450 identifies the input features from the network page 113. The input features are reformatted into HDML type links. A function is associated with selection of the link. Therefore, each input feature provided on network site 430 is provided an HDML type link that is included in content 114. The HDML link is also provided with coding to instruct conversion engine 450 when the corresponding is selected. The functionality of the coding is described below.

Once network page 113 is rendered on mobile device 460, the user can make a subsequent request 115 by selecting one of the HDML links that correspond to input features provided on network site 430. The user makes request 115 to signal a wish to make a specific input entry. Preferably, each HDML link is displayed with features such as wording or graphics so as to clearly indicate a wish by the user to make an entry for the input feature associated with that HDML link.

The request 115 is signaled to conversion engine 450 in HDML. The HDML link on which request 115 was generated includes code to enable conversion engine 450 to recognize the link as corresponding to a particular input entry on network site 430. In an embodiment, the code provided with the HDML link instructs conversion engine 450 to open and access a new network site 455. The new network site is preferably virtual, so that it exists only for the purpose of providing a platform for the user to signal input entries. \

Signal 116 opens virtual site 455 according to code provided with the link from mobile device 460. Alternatively, code may be provided by conversion engine 450 to open virtual site 455. Once opened, a page 117 is retrieved from virtual site 455. The page is transmitted to mobile device 460 via  
5 signal 118, where the page for the virtual site 455 is rendered in HDML.

The user of mobile device 460 may enter input for virtual site 455. The input corresponds to what the user would enter in the corresponding input feature of network site 430, had the user been using a CHTML device. The mobile device signals input 119 to conversion engine 450. The conversion  
10 engine 450 converts input 119 into CHTML. The input 560 is signaled to network site 430 in CHTML, where it is entered.

Alternatively, the input 560 may be signaled to an internal network site 432, corresponding to where entry into input feature on the network page would be entered on network site 430. In some applications, entry into input features  
15 of network site 430 are equivalent to selecting internal links for other network sites. Thus, entry into virtual site 455 may subsequently be treated as selection of an internal link on network site 430.

The response 121 to entering the input entry for network site 430 is retrieved in CHTML. The response 122 is then signaled to mobile device 460.

20 An advantage provided by an embodiment of the invention is that HDML type mobile devices are provided the ability to perform tasks and functions that were not previously available. In particular, HDML type mobile devices 160 may be used with network sites that allow for multiple input features and entries. For example, with an embodiment of this invention,



The signal **211** is a request from mobile device 560 to retrieve a page from a network site. The request is in the form of a card that provides the address of the network site being requested. The request **211** may also identify mobile device 560, including its language type.

5           In this illustration, mobile device 560 is assumed to be an HDML type device. The conversion engine transmits a request **212** to database 545. The request **212** provides DMS 548 with the selected network site and the type of mobile device 560 being used. A look-up table may be used, for example, to correlate the identification of mobile device 560 with a language. The DMS 548  
10       selects instructions for converting the network page for the requested site to the language of the identified mobile device. The instructions **213** are signaled to conversion engine 550. Using the instructions, conversion engine 550 signals a request **214** to retrieve content from the network site selected on mobile device 560. A corresponding network page **215** is retrieved. The network page is  
15       converted by conversion engine 550 using the instructions from database 545. The converted network page **216** is signaled to mobile device 560.

          It will be appreciated that in this system, mobile device 560 may use HDML, WML, CHTML, or other programming to communicate with network sites. The conversion engine is able to identify the type of device, as well as the  
20       selected destination of the user on an associated network. One function that can be performed by conversion engine 550 is to convert communications to and from mobile device 560 and network site between HTML or CHTML to HDML.

It an embodiment, a user defined database may be coupled to the system 600 to enable conversion engine 550 to use user-defined parameters in accessing network sites. Additional description of this feature is described with U.S. Patent App. No. 09/513,554, entitled *System and Automatic Data Retrieval* 5 *on an Internet Protocol Network*, to Ndili et al., filed on February 25, 2000, which is incorporated by reference in this application.

FIG. 7 illustrates a process that details conversion engine 550 interacting with mobile device 560, under an embodiment of the invention. For illustration, the process is described with reference to a uniform resource locator (URL) for 10 an Internet site containing CHTML files. The mobile device 560 is assumed to be an HDML type device. Reference to elements of FIG. 6 is intended to be for illustrative purposes only.

In step 580, conversion engine 550 receives a card from mobile device 560. The card specifies an address, preferably in the form of an URL. The 15 address is to locate the network site being requested by the use of mobile device 560. This communication is transmitted through a wireless medium in HDML.

In step 582, the conversion engine 550 signals DMS 548 the card received from mobile device 560. The DMS 548 is able to use information provided with the card to retrieve a set of instructions from database 545. The 20 instructions are to programmatically control conversion engine 550 to assemble content accessible by the URL for mobile device 560. The conversion engine 550 may communicate with DMS 548 over a network such as the Internet. If the selected Internet site includes HTML or CHTML resources, the instructions include commands to "fetch" the URL, display the header and title for the URL,

remove or replace header tags, display a welcome message provided on the URL, and exact a pertinent section of the web page located by the URL.

In particular, if the requested network site includes CHTML, the instructions provided by DMS 548 may be to replace tags formatted for CHTML with tags formatted HDML. With CHTML pages, the instructions may cause conversion engine 50 to remove images, such as provided in "jpg" format. Other restructuring and formatting features may be included with the instructions to effectively convert communications between mobile device 560 and the selected CHTML site.

10 In step 584, the conversion engine 550 accesses the network site located by the URL to retrieve specific network sites. The network site is identified from the request signaled by mobile device 560.

In step 586, conversion engine 550 converts the page retrieved from the network site into HDML. In step 588, the content or network page is transmitted in the wireless protocol to mobile device 560. The network event or content may be formatted or otherwise paginated for a display of mobile device 560.

As described with embodiments of FIGS. 3 and 4, the instructions may also provide arguments and code to be included with internal links located on the requested network site. The arguments and code enable mobile device 160 to signal the internal network site using the corresponding link.

Further, as described with FIG. 5, an embodiment may provide for the instructions to direct conversion engine 550 to signal input features provided by the requested network site 530 as selectable links. The links may be selected to render a new network page for the mobile device. The user of the mobile device



560 may signal input using the created network page. The input is then forwarded to network sites located by the input features. This feature of the invention is particularly useful when the mobile device operates in HDML, and the network site is coded in HTML or CHTML.

5    E. Converting Between Languages For The Mobile Device

FIG. 8 illustrates a method performed by content engine 550 in paginating the network event into the wireless format. A process such as described with FIG. 8 enables events to be retrieved from IP sites and then converted for mobile devices 560. The content appearing on mobile device 550  
10    is properly paginated for the screen of the mobile device 560, with no modification at the network site or mobile device 560. The process described with FIG. 8 assumes that content engine 550 has retrieved the network content from the network 135.

In step 590, a memory allotment is specified for mobile device 560. The  
15    memory allotment depends on the wireless protocol in use, and the desired page size which can be a function of the screen size of target mobile device 560. The memory allotment may be designated as, for example, 1k, representing the average screen sizes WAP pages for mobile phones. Alternatively, a user of mobile device 560 may configure the memory allotment depending on the  
20    specific type and model of mobile device 560 being used. In an embodiment, the memory allotment is specified through user database 125.

In step 492, the content retrieved from the IP site is segmented according to the memory allotment. Each segment is portioned to correspond

approximately to the memory allotment. The size of the segments allow each segment to be displayed in its entirety as one page on mobile device 550. As an example, if a journal article on a web site is 24k in length, the article is segmented roughly into 24 1k segments.

- 5           In step 494, a page break line or region is located on the retrieved network content corresponding to the boundary of each segment. The content engine 550 may locate a line or region where the 1k break occurs.

Then in step 495, each segment is paginated on that page break line or region to ensure that the cut-off to a next segment is made at an appropriate place. If a segment of network content retrieved from the IP site is not paginated, HTML or CHTML coding may not correctly be converted to WML or HDML. In addition, words may be split up to appear on different pages on mobile device 550.

In an embodiment, a free unattached space is located to correctly paginate each segment on the page break line or region. For HTML or CHTML coding, the free unattached space is positioned outside of tags and other coding appearing on that portion of the network content. Specifically, the content engine 550 locates spacing outside of HTML open end and close end tags. As an example, the line of coding appearing on a page break line may be:

20           <a href = www.mobileshift.com> click here <br> to see </a>

The content engine 550 identifies spaces before "<a href", and after "</a>" as places where a page break may occur. The content engine 550 ignores spacing falling between the opening and closing of the <a>....</a> tags. In this way, the page displayed on the screen of mobile device 550 contains entire

words and code segments, and is coded from HTTP to WML or HDML appropriately.

To ensure the free unattached space is between an open or closed bracket, the content engine 550 may include coding that measures on the page  
5 break line the distance between the first located space and an open tag "<". The coding then measures the space between the located space and the closed tag ">". If the distance between the located space and the open tag is less than the distance between the located space and the open tag, then the located space is considered free and unattached. The located space is then made the location of  
10 a page break.

If the distance between the located space and the open tag is greater than the distance between the located space the close tag, then the located space is considered attached. A next space is then located on the break line. The next space may correspond to the space appearing to the right of the close tag. The  
15 spaces appearing on the page break line are checked in this manner until a free unattached space is located. Once the free unattached space is located, the segment is paginated.

In step 496, the segment is signaled to mobile device 560. The segment may be signaled with a user-interactive feature (icon) to signal a request for a  
20 next segment. In step 498, a determination is made as to whether a next segment is the last segment for the network content. If in step 498, a next segment is a last segment, then the last segment is signaled to mobile device 550 in step 499 as the last segment. If there is another segment, then steps 496-499 are repeated.

1993 1994 1995 1996 1997 1998 1999 2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100 2101 2102 2103 2104 2105 2106 2107 2108 2109 2110 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120 2121 2122 2123 2124 2125 2126 2127 2128 2129 2130 2131 2132 2133 2134 2135 2136 2137 2138 2139 2140 2141 2142 2143 2144 2145 2146 2147 2148 2149 2150 2151 2152 2153 2154 2155 2156 2157 2158 2159 2160 2161 2162 2163 2164 2165 2166 2167 2168 2169 2170 2171 2172 2173 2174 2175 2176 2177 2178 2179 2180 2181 2182 2183 2184 2185 2186 2187 2188 2189 2190 2191 2192 2193 2194 2195 2196 2197 2198 2199 2200 2201 2202 2203 2204 2205 2206 2207 2208 2209 2210 2211 2212 2213 2214 2215 2216 2217 2218 2219 2220 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520 2521 2522 2523 2524 2525 2526 2527 2528 2529 2530 2531 2532 2533 2534 2535 2536 2537 2538 2539 2540 2541 2542 2543 2544 2545 2546 2547 2548 2549 2550 2551 2552 2553 2554 2555 2556 2557 2558 2559 2560 2561 2562 2563 2564 2565 2566 2567 2568 2569 2570 2571 2572 2573 2574 2575 2576 2577 2578 2579 2580 2581 2582 2583 2584 2585 2586 2587 2588 2589 2590 2591 2592 2593 2594 2595 2596 2597 2598 2599 2600 2601 2602 2603 2604 2605 2606 2607 2608 2609 2610 2611 2612 2613 2614 2615 2616 2617 2618 2619 2620 2621 2622 2623 2624 2625 2626 2627 2628 2629 2630 2631 2632 2633 2634 2635 2636 2637 2638 2639 2640 2641 2642 2643 2644 2645 2646 2647 2648 2649 2650 2651 2652 2653 2654 2655 2656 2657 2658 2659 2660 2661 2662 2663 2664 2665 2666 2667 2668 2669 2670 2671 2672 2673 2674 2675 2676 2677 2678 2679 2680 2681 2682 2683 2684 2685 2686 2687 2688 2689 2690 2691 2692 2693 2694 2695 2696 2697 2698 2699 2700 2701 2702 2703 2704 2705 2706 2707 2708 2709 2710 2711 2712 2713 2714 2715 2716 2717 2718 2719 2720 2721 2722 2723 2724 2725 2726 2727 2728 2729 2730 2731 2732 2733 2734 2735 2736 2737 2738 2739 2740 2741 2742 2743 2744 2745 2746 2747 2748 2749 2750 2751 2752 2753 2754 2755 2756 2757 2758 2759 2760 2761 2762 2763 2764 2765 2766 2767 2768 2769 2770 2771 2772 2773 2774 2775 2776 2777 2778 2779 2780 2781 2782 2783 2784 2785 2786 2787 2788 2789 2790 2791 2792 2793 2794 2795 2796 2797 2798 2799 2800 2801 2802 2803 2804 2805 2806 2807 2808 2809 2810 2